




- + Capacity: 47 bottles\*:  
- upper part: 22 bottles  
- lower part: 25 bottles
- + Vinotag compatible\*\* 
- + Free standing and built-under counter installation
- + Design: black body door frame
- + Cooling system: compressor
- + Type of cold: air moving system
- + Adjustable temperature ranges of use:  
- upper part: 5°-12°C  
- lower part: 12°-20°C
- + Electronic regulation
- + Thermometer with white electronic display
- + White LED lights with switch button
- + Humidity control: water tray
- + 1 glass door, anti-UV treated, 3-layers tempered glass (grey-colored)

#### FULL OPTION RANGE

The PANEL range is equipped with wooden shelves on telescopic rails with labels prominent.

Adapt the colour of the lighting and its intensity according to the atmosphere of the kitchen. Choose between 3 colours (Cool White, Warm White, Amber) and 4 intensity levels (25%, 50%, 75%, 100%).

#### THE BEST OF INSTALLATION

The PANEL range brings together the best for easy installation in any kitchen.

With the PANEL range, install a panel identical to the front of the kitchen for optimum integration.

A 2 cm recess plinth for perfect alignment.

A removable plinth to pass any perforated kitchen plinth. (Total of 7.5 cm)

A plumbing passage at the back so that no space is lost in the product recess.

#### CONNECTED 24 H

Equipped with a remote-control function, you can control the temperature, lighting, and alarms, from the Vinotag @ app, at any time, from your smartphone.

Thanks to temperature alerts, you can be alerted at any time to make a quick decision to protect your precious bottles.

Frame not supplied



## Eco-responsibility

Our products are manufactured in compliance with European environmental rules. Especially, refrigerant fluid (R600a) doesn't reject neither CFC nor HFC and respect environment.

Energy consumption is calculated based on the result obtained for 24h in standard test conditions. The actual energy consumption depends on the conditions of use and location of the device.


This equipment is designed to be used in an ambient temperature between 10°-38°C.

This appliance is intended to be used exclusively for the storage of wine.

Alcohol abuse is dangerous for health, please consume in moderation.

\*Capacity given as an indication with 75cl Bordeaux traditional type bottles and measured with 4 shelves. Adding shelves reduce considerably the total capacity.

\*\*Thanks to the Vinotag® application, benefit from a digital register of your wine cellar and be alerted of the peak dates of your wines. In partnership with Vivino, scan your bottle to access its pre-filled wine sheet.



> EQUIPMENTS INCLUDED

- 4 sliding wooden shelves (beech)
- 4 adjustable feet (height 7 cm)
- Plumbing passage
- Anti-vibration system
- Removable ventilation grid

> TECHNICAL CHARACTERISTICS

- Energy class: F
- Annual electrical consumption: 103 kWh
- Climatic class: SN-ST
- Noise level: 37 dB
- EEI: 122.00
- Voltage: 220-240 V
- Power input: 80 W
- Category: 2 - Wine cellar
- Type of gas: R600a

> SAFETY

- **Visual and audible alarms:** notify you when your attention is required

> VINOTAG® APPLICATION

Free wine cellar management application. Access a virtual representation of your wine cellar and a detailed inventory of its contents.

> COMPATIBLE ACCESSORIES

Only available in spare parts

> LOGISTIC DATAS

Gross dimensions (WxDxH cm)	: 65 x 61 x 85
Net dimensions (WxDxH cm)	: 59,5 x 57 x 81,7
Gross weight (kg)	: 46.00
Net weight (kg)	: 42.00
Full truck (pcs)	: 0
Container (pcs)	20' : 0
	40' : 0
	40' HC : 170

Gencod 3595320108057